

EcononebTechnical specifications



EcononebTechnical specifications



Econoneb		
Dimensions	210 x 210 x 185mm	
Weight	2.7kg	
Electrical Requirements	220 - 240V or 50 - 60Hz	
Flow Rate	7 - 9 L/min at 138 kPa*	
Particle Size	MMAD 3.4 microns*	
% Fine Particle Fraction	70% of particles <5 microns*	
Aerosol Output Rate	0.39ml per minute**	
Compliance	Electrical Safety Class II Type BF. Continuous use. Class IIa MDD 93/42/EEC CE 0120	
Accessories Included	Microneb III nebuliser chamber x 1, driveline x 1, adult face mask x 1, child face mask x 1, mouthpiece x 1, inlet filter x 1, outlet filter	

Product	Part Codes	
Econoneb (UK Plug)	3605040HW	
Econoneb (EU Plug)	3605042HWEU	
Adult Year Pack	L3605122	
Child Year Pack	L3605123	

^{*} Measured in accordance with BSEN 13544-1

Product information

The Econoneb is a powerful compressor that is continuously rated, making it a cool running nebuliser for demanding use. It is a reliable unit which is ideal for meeting the challenges of both hospitals and clinics. The Econoneb has a high flow rate which is suitable for nebulising bronchodilators (relievers), corticosteroids (preventives) and antibiotics.

- Includes a 3 year guarantee motor only
- Continuously rated, remains cool during constant use
- Powerful compressor
- Reliable performance
- Easy carrying handle
- Comes complete with a starter pack, ready for immediate use

^{**} Values will vary depending on viscosity of solutions being nebulised